


Cable

5E UTP 350MHz Enhanced Cable



24 AWG Cat5E CMR, High-Performance Data Cable

APPLICABLE STANDARDS

• ETL Listed Type CMR	• C(ETL) listed CMG FT4
• ETL Verified to TIA - 568-C.2, and ISO/IEC 11801	
• ROHS Compliant	• ATM 155 Mbps
• Ethernet 10BASE-T, 100BASE-TX, 100BASE-VG, 100BASE-T4	
• 1000 Mbps 1000BASE-T Gigabit Ethernet (IEEE 802.3)	
• 16 Mbps Token Ring™ (IEEE 802.5)	

PHYSICAL CHARACTERISTICS

Number of Conductor Pairs	4
Size	24 AWG
Stranding	Solid
Conductor Material	Solid Annealed Bare Copper
Shield Material	Unshielded
Rip Cord	Yes
Insulation Material	Polyethylene
Insulation Overall Diameter	0.035 in. + 0.0002 in.
Insulation Average Thickness	0.0081 in.
Jacket	Flame Retardant PVC
Outer Jacket Average Wall Thickness	0.023 in.
Outer Jacket Nominal O.D.	0.200 in. + 0.008 in.
Nominal Weight	21 lbs.
Voltage Rating	300V

MECHANICAL CHARACTERISTICS

Temperature Rating	Installation	0 to +60°C
	Operating	-20°C to + 75°C
Tensile Strength	Before	>= 13.8 Mpa
Elongation	Aging	>= 100%
Aging Condition		100°C x 240 hours
	After	> = 85% of unaged
	Aging	> = 50% of unaged

COLOR CODE

Pair 1	White / Blue	Blue
Pair 2	White / Orange	Orange
Pair 3	White / Green	Green
Pair 4	White / Brown	Brown

CABLE MARKING

CATEGORY 5E 350MHZ 24AWG 4 PR
UTP XXXXXX CRT CMR C(ETL)US ETL
LISTED & VERIFIED TO TIA-568-C.2
***FT





ELECTRICAL PERFORMANCE

* Values above 100MHz are information only

Frequency (MHz)	Attenuation (dB/100m)		Return loss (dB)		NEXT (dB)		PS-NEXT (dB)		ELFEXT (dB)		PS-ELFEXT (dB)		ACR (dB)		PS-ACR (dB)	
	Max.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Max.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.
0.772	11.8	1.5	23.0	33.0	72.0	81.1	70.0	78.7	66.0	73.3	63.0	72.7	70.2	79.2	68.2	77.0
1	2.0	1.8	23.0	38.6	70.3	79.4	68.3	76.9	63.8	71.3	60.8	70.6	68.2	77.6	66.3	75.0
4	4.1	3.6	23.0	39.8	61.2	69.9	59.3	67.4	51.7	59.4	48.7	58.7	57.2	66.3	55.2	63.5
8	5.8	5.1	24.5	38.2	56.8	61.9	54.8	59.4	45.7	53.2	42.7	51.1	51.0	59.8	49.0	56.9
10	6.5	5.8	25.0	38.0	55.3	62.4	53.5	59.9	43.8	50.5	40.8	49.7	48.8	56.6	47.0	53.7
16	8.2	7.4	25.0	37.4	52.3	57.8	50.3	55.2	39.7	47.0	36.7	45.1	43.0	53.0	42.1	47.4
20	9.3	8.2	25.0	36.8	50.8	56.4	48.8	53.8	39.7	45.0	34.7	43.6	41.5	50.5	39.5	45.0
25	10.4	9.3	24.3	35.2	49.3	56.3	47.3	53.6	35.8	43.3	32.8	42.0	38.9	47.0	36.9	43.7
31.25	11.7	10.5	23.6	33.3	47.9	53.8	45.9	51.1	33.9	41.3	30.9	40.5	36.5	43.3	34.2	40.0
62.5	17.0	14.9	21.5	32.2	43.4	49.8	41.4	47.4	27.8	35.8	24.8	34.5	26.4	35.0	24.4	31.2
100	22.0	19.2	20.1	31.3	40.3	47.5	38.3	45.0	23.8	31.3	20.8	30.3	18.3	26.2	16.3	24.2
155	28.1	24.2	18.8	29.8	37.4	45.1	35.4	42.6	19.9	27.5	16.9	26.9	10.0	20.9	7.3	15.9
200	32.4	27.3	18.0	28.5	35.7	43.3	33.7	40.2	17.7	24.7	14.7	24.5	15.0	16.0	12.0	10.0
250	38.9	30.9	17.5	27.3	34.8	41.4	32.5	39.0	17.1	22.2	14.0	22.5	0.0	10.6	-	4.0
300	41.0	34.1	16.8	25.6	33.1	40.2	31.1	37.7	16.7	20.5	13.5	20.7	-	6.1	-	-1.3
350	44.9	37.8	16.3	23.2	32.1	39.0	30.1	36.5	16.0	19.4	12.8	19.6	-	1.2	-	-6.4



COLOR CODE

Maximum Conductor DC Resistance @ 20°C	9.65 Ω / 100
Meters Maximum DC Resistance Unbalanced @ 20°C	5%
Maximum Pair-to-Pair Ground Capacitance Unbalance	330 pF / 100 Meters
Characteristic Impedance (1350 MHz)	100 + 15 Ω
Mutual Capacitance	5.6 nF / 100
Meters Maximum Dealy Skew	40 ns / 100 Meters

PART NUMBERS

PartNumbers	Color	Put-up		PartNumbers	Color	Put-up	
5E04URBK4	Black	1.000'	Reelex II	5E04URPK4	Pink	1.000'	Reelex II
5E04URBL4	Blue	1.000'	Reelex II	5E04URPR4	Purple	1.000'	Reelex II
5E04URGN4	Green	1.000'	Reelex II	5E04URRD4	Red	1.000'	Reelex II
5E04URGY4	Grey	1.000'	Reelex II	5E04URWH4	White	1.000'	Reelex II
5E04UROR4	Orange	1.000'	Reelex II	5E04URYL4	Yellow	1.000'	Reelex II